



PRODUCT INFORMATION LiteTable-ST-Schu_TY_US - 16.12.2021 - www.vsamerica.com

LiteTable-ST Stackable table.

Frame made from welded round tubular steel legs with all-round rectangular tubular steel top frame, all powder-coated. Because the inner and outer legs are arranged in pairs, the table is stackable. What is more, they can be rotated to form continuous rows. The edge of the top frame is equipped with stacking and glide protection. Tables with glides for hard or soft floors or with 2-component universal glides an, optionally, with two castors at outer legs. Models with LIGNOdur top optionally available with four castors.

Table sizes according to DIN EN 1729 in fixed heights. Models with LIGNOdur top optionally with step height adjustment with hexagon screw fastening.

Tabletop with a melamine or laminate-coated LIGNOpal chipboard top and glued plastic edge or a HPL top with round or spare corners.

Warning: A maximum of four stacked (unloaded) tables may be moved together on castors; tables with LIGNOdur tops are not recommended to be moved when stacked, due to weight.

The following material groups are available to choose from: Frame made of steel: M1; Top made of chipboard: L4; Top made of chipboard with PUR edge: L2; Chipboard with laminate: L9; HPL-top: L4.

		Table heights ($\pm 7/8$ inch) as per DIN EN 1729 ○ 0 = 15 $3/4$ inch ● 2 = 20 $7/8$ inch ● 3 = 23 $1/4$ inch ● 4 = 25 $1/4$ inch ● 5 = 28 inch ● 6 = 30 inch ● 7 = 32 $3/8$ inch		* w-d footprint		
LiteTable-ST	PUR/KU	d = 21 $5/8$ inch		21090		21003
	KU	d = 25 $5/8$ inch			21091	
		w inch		27 $5/8$	29 $1/2$	
		Fixed height		11 $7/8$ inch	○ 2 ● 3 ● 4 ● 5 ● 6 ● 7	
		max. stacking height		8		
		max. stack w* inch		30 $3/4$	32 $3/4$	
		max. stack d* inch		32 $3/8$	36 $1/4$	
		Weight min. lb		29,7	33	